

PRE-USE CHECKS

CONCRETE WASHOUT SYSTEM

Pre-use, any faults should be reported to your Supervisor. If the equipment should become faulty during your working day, stop immediately, and report the fault to your Supervisor. Defective equipment should not be used until the fault is rectified. Contact Conquip to book an engineer visit or to arrange for the refurbishment of any defective equipment.

✓ Safe to use ✗ Not safe to use

	NO.	DAILY CHECK	MON	TUE	WED	THU	FRI	SAT	SUN
PLATFORM	1	Harness point secure							
	2	Handrails secure and not damaged							
	3	Gate operation							
	4	Lift points bent or worn							
	5	Adjustment brackets in place							
	6	Adjustment cross bar in place							
	7	Linch pins present							
	8	General visual framework inspection							
FILTRATION TRAY	1	Lift points bent or worn							
	2	Bulk bag rails in place							
	3	Pump chamber cover plate in place							
	4	Pump and hose connected							
	5	Heel pins damage							
	6	Heel pin retaining clips in place							
	7	General visual body inspection							
WATER TANK	1	Hose arm assembly in place							
	2	Water hoses damaged							
	3	Electric supply damage							
	4	Lift points bent or worn							
	5	General Visual framework inspection							
	6	General visual tank inspection							
	7	Pump working							

WRITE DEFECT HERE

Defect Report to:

Date:

Sign:

Print: