

USER GUIDE

CONCRETE WASHOUT FRAME





DISCLAIMER

Do not attempt to handle or operate this equipment before you have received sufficient training. Before use, operatives must have carried out all checks featured on the Visual Inspection Sheet on page 11. It is imperative that you have read the General Safety Instructions on page 12 and sufficiently familiarised yourself with the Operational Procedures in this document.

Note that this item is compliant only to the standards specified in this User Guide and it is therefore the duty of the responsible person(s) to review and ensure compliance.

CONTENTS

PRODUCT INFORMATION

INTRODUCTION 04

SPECIFICATION 05

PARTS DIAGRAM 07

OPERATIONAL PROCEDURES

IMPORTANT USAGE NOTES 08

SET UP INSTRUCTIONS 08

USAGE INSTRUCTIONS - STANDARD FILTRATION BAG 08

USAGE INSTRUCTIONS - PRE-TREATED FILTRATION BAG 09

MAINTENANCE & INSPECTION

MAINTENANCE REGIME 10

VISUAL INSPECTION SHEET 11

GENERAL SAFETY INSTRUCTIONS

SAFETY INSTRUCTIONS 12

GENERAL NOTES 13

LEGAL

TERMS AND CONDITIONS 14

EC DESIGN CONFORMITY 18

STANDARDS AND REGULATIONS APPLICABLE 19

INTRODUCTION

OVERVIEW

The Conquip Concrete Washout Frame is used to wash concrete truck chutes and smaller concrete equipment on-site.

A steel bag holding basket with holes in the base holds a filtration bag that captures the heavy concrete aggregate from washout, while allowing the wastewater to filter into a sump below. As the concrete equipment is washed, the wastewater filters through the porous material and into the sump where it can be treated with pH neutraliser additive and tested.

Once the pH level has been sufficiently reduced, the wastewater can be safely disposed of without polluting the environment, complying with current environmental regulations.

KEY BENEFITS

- Quick and easy to set up and use.
- Compact unit that takes up minimal space on-site.
- Sites can wash down equipment from multiple sides of the unit.
- Prevents contaminated water from concrete washout polluting the local environment.
- Captures large aggregate and solids in the filtration bag that can be easily disposed of.
- The unit can be supplied with 25kg containers of pH neutraliser additive with the corresponding Material Safety Data Sheet (MSDS) and litmus test kits, if required.
- Fork pockets and designated lifting points for easy manoeuvre around site when empty.

OPTIONAL EXTRAS

- A pre-treated filtration bag (lined with pH neutraliser additive) can be provided instead of our standard filtration bag, if preferred.

support@cqegroup.com | +44 (0) 333 300 3470 | www.cqegroup.com

PRODUCT INFORMATION

SPECIFICATION




CODE	WEIGHT (kg)	WLL* (kg)
CS255AA	340	Self Weight

*Working Load Limit

support@cqegroup.com | +44 (0) 333 300 3470 | www.cqegroup.com


SPECIFICATION

ITEM	PRODUCT CODE
Concrete Washout Frame	CS255AA



LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)
1210	1505	1285

PARTS DIAGRAM



ITEM NUMBER	PART	DESCRIPTION	QUANTITY
1	N/A	Bag Holding Basket	1
2	N/A	Deflector	1
3	ZZ991247	3” BSPT Socket Female	1
4	ZZ991247	3" Male Plug	1
5	NS800454	Plain Washer M12 G8	4
6	NS800481	Hex Head Bolt M12x1.75 x 120	4
7	ZZ990464	Decal: Refer To Instruction Manual/Booklet	1
8	ZZ991093	Decal: Conquip White Logo 1000 x 165mm	2
9	ZZ960341	Standard Filtration Bag 1000mm x 1000mm x 1000mm	1

NOTE: These parts are for this model, they may differ for previous versions. Please contact Conquip with any queries.

OPERATIONAL PROCEDURES

IMPORTANT USAGE NOTES

- Do not attempt to wash concrete skips using this system. Conquip offers a range of alternative solutions for this.
- Ensure the filtration bag is correctly fitted and secure. Do not overfill the filtration bag as it could be difficult to remove.
- If using a pre-treated filtration bag, check the maximum number of washes with the bag manufacturer. Replace when required to avoid contamination risk.
- Only lift the Concrete Washout Frame when it is empty.
- Always follow the site's environmental guidelines and policies regarding the disposal of concrete waste and wastewater.

ASSEMBLY INSTRUCTIONS

01. Using two operatives, lift the deflector off the top of the unit and place it to one side.
02. Fit the filtration bag into the bag holding basket and replace the deflector to secure the bag in place.
03. The Concrete Washout Frame is now ready to use.

USAGE INSTRUCTIONS

STANDARD FILTRATION BAG

01. Add around half of a 25kg container of pH neutraliser additive to the sump.
02. Position the equipment or concrete truck chute to be washed over the opening of the Concrete Washout Frame.
03. Wash the concrete residue and aggregate off the item. Large aggregate and solids will be captured in the filtration bag while the wastewater flows through the porous material and into the sump.
04. Once washout is complete, remove the filtration bag and dispose of any concrete aggregate and solids, following the site's process for handling hardened concrete waste.
05. Use litmus test kits to check the pH level of the wastewater in the sump. If the pH level is too high, add more pH neutraliser additive to further treat it. The sump has a capacity of 250 litres, use the chart on page 09 for guidance on how much pH neutraliser may be required.
06. Once the wastewater has been tested to ensure it has been sufficiently treated, it can be safely disposed of in line with the site's environmental guidelines.

support@cqegroup.com | +44 (0) 333 300 3470 | www.cqegroup.com

OPERATIONAL PROCEDURES

07. Fit a new bag in the frame and replace the deflector.
08. The Concrete Washout Frame is ready to use again.



PRE-TREATED FILTRATION BAG

01. Position the equipment or concrete truck chute to be washed over the opening of the Concrete Washout Frame.
02. Wash the concrete residue and aggregate off the item. Large aggregate and solids will be captured in the pre-treated filtration bag while the wastewater flows through the porous material and into the sump.
03. As the wastewater passes through the walls of the filtration bag (lined with pH neutraliser additive), it is treated, resulting in a pH level of around 8.5 once it has collected in the sump. Fine chalk created from this pH level adjustment process discharges into the water in the sump and slowly begins to settle, further reducing the pH level.
04. Once washout is complete, remove the deflector and the filtration bag, Dispose of any hard concrete aggregate and solids, following the site's process for handling hardened concrete waste.
05. The treated wastewater can be disposed of in line with the site's environmental guidelines. The bag and deflector can then be refitted ready for use again. Always check with the bag manufacturer for the amount of uses of one pre-treated filtration bag, as these may vary.
06. Conquip always recommend testing wastewater before disposal to prevent contaminating the environment.

support@cqegroup.com | +44 (0) 333 300 3470 | www.cqegroup.com

MAINTENANCE & INSPECTION

MAINTENANCE REGIME

- It is mandatory that the equipment is thoroughly examined regularly, by a qualified engineer, to ensure compliance with relevant regulations. Conquip recommend carrying out a thorough examination every six months.
- This equipment may incorporate various loose and detachable items including, but not limited to pins, bolt assemblies and adaption plates. Refer to the separate requirements for the safe use of those items.
- When not being used, store the unit in a clean, upright condition and in a safe place where it will be protected from thieves and unauthorised users.
- This equipment must be inspected by the responsible person before each use and then regularly, as determined by your risk assessment or working practice. If you have any concerns about the machinery's condition or suitability, do not use it.

VISUAL INSPECTION CHECKLIST

INSPECTION ITEMS	RESULTS		COMMENTS
	PASS	FAIL	
Serial Number			CQ.....
Product Code			
Working Load Limit (kg)			
Conforms to user guide specification			
Check sump for damage or leaks			
Check lifting points for wear or damage			
Check fill level of bag and empty if required			
Check filtration bag is fit for purpose and replace if required			
Carry out a general visual inspection of the body			

SIGNATURE			
Name	Position	Qualification	Signature & Date

GENERAL SAFETY INSTRUCTIONS

The equipment should be properly operated and maintained to keep it in a safe, efficient operating condition. Be sure that all fixings and components are free of mud or other matter that might cause issues hazardous to the operator, serviceman, or other personnel or equipment. Report all malfunctions to those responsible for maintenance, and do not operate the equipment until corrected. Normal service or maintenance performed as required can prevent unexpected and unnecessary downtime.

This operations manual describes general inspections, servicing and operation with the normal safety precautions required for normal servicing and operating conditions. It is not a guide, however, for abnormal conditions or situations, and therefore, servicemen and operators must be safety conscious and alert to recognise potential servicing or operating safety hazards at all times, and take necessary precautions to assure safe servicing and operation of the equipment.



M002
Refer to instructions manual



M004
Wear eye protection



M008
Wear safety footwear



M009
Wear protective gloves



M010
Wear protective clothing



M014
Wear head protection



M015
Wear high-visibility clothing

GENERAL NOTES

- Read this operations manual and learn the operating characteristics and limitations of the equipment. Know what operating clearances the equipment requires.
- Read and understand all the safety signs prior to operation.
- If the safety signs are obstructed by dirt or debris, clean them using mild soap and water prior to operation.
- If the safety signs are damaged or illegible, replace them immediately, prior to operation.
- Be aware of operating hazards that weather changes can create on the job. Know proper procedures to follow when a severe rain or electrical storm strikes.
- Never attempt to operate or work on machinery when not feeling physically fit.
- Never wear loose clothing, rings, watches, heavy gloves etc., that might catch and result in injury.
- Know what safety equipment is required and use it. Such equipment may be: hard hat, safety glasses, reflector type vests, protective gloves and safety footwear.

MATERIALS SAFETY DATA SHEET

- Below are the contact details for the manufacturer of the pH neutraliser additive.
- For the full Material Safety Data Sheet (MSDS) please click here.

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE	
Product name	pH Blue
Use of substance / mixture	Construction materials
DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET	
Company name	Mudtech Ltd
Address	Wyburn House 1 Crab Lane Stafford Staffordshire ST16 1SB
Tel:	+44 (0) 1929 551 245
Fax:	+44 (0) 1929 554 361
Email:	sales@mudtech.co.uk

TERMS & CONDITIONS

CONQUIP ENGINEERING GROUP STANDARD PRODUCT WARRANTY

01. COMMENCEMENT

1.1 This Warranty shall commence on the Commencement Date and shall continue until the earlier of:

(a) the Expiry Date; or

(b) the date on which it may be voided in accordance with clause 4.1(b)

when it shall terminate automatically without notice.

02. DUTY OF GOOD FAITH

2.1 The Purchaser shall in the exercise of its rights under this Warranty and in the compliance with its obligations under this Warranty be subject to and shall in all respects owe and comply with a duty of good faith to the Warrantor.

03. NATURE AND EXTENT OF COVER

3.1 Subject to clause 3.2 the Warrantor agrees and undertakes to the Purchaser that it shall be liable to the Purchaser under and in accordance with the terms of this Warranty in the event that:

(a) prior to the Expiry Date the Purchaser shall notify a Warranty Claim to the Warrantor; and

(b) the Equipment or any relevant part of the Equipment shall have become unusable as the result of defective material or defective workmanship prior to the Expiry Date.

3.2 The Warrantor's obligation under clause 3.1 shall be expressly subject to the provisions of clauses 4, 5 and 6 and conditional upon the Purchaser's compliance in full with the provisions of clause 7.

04. RESTRICTIONS

4.1 The following restrictions apply to this Warranty:

(a) This Warranty is personal to the Purchaser and neither the legal benefit nor legal burden of this warranty may be assigned or novated or otherwise transferred by the Purchaser to any other party. Any purported assignment, novation or transfer shall not be binding upon the Warrantor.

(b) This Warranty shall be void in the event that the Purchaser:

(i) cannot provide authentic and original documentary evidence that the Purchaser has during the period between the Commencement Date and the Expiry Date complied with the Maintenance and Servicing Requirements; and/or

(ii) has, during the period between the Commencement Date and the Expiry Date, exceeded the Purchaser's Usage Cycle Parameters; and/or

(iii) has, during the period between the Commencement Date and the Expiry Date, exceeded the Purchaser's Use Parameters; and/or

(iv) has carried out, or procured the carrying out by any third party of, any repair to the Equipment or any part of the Equipment which is not an Authorised Repair; and/or

(v) has operated the Equipment after having replaced any part of the Equipment with a part which has not been supplied and fitted by the Warrantor; and/or

(vi) has modified the Equipment in any way prior to use.

05. EXCLUSIONS

5.1 The following are excluded from the scope of this Warranty:

(a) Loss of and/ or damage to the Equipment or any part of it resulting from any collision between the Equipment and any other fixed or stationary or mobile object whatsoever, irrespective of whether that collision was or was not caused by the Purchaser; and/or

(b) Loss of and/or damage to any personal property and/or possessions or other equipment not forming part of the Equipment but which is present in or about the Equipment; and/or

(c) loss and/or damage which is covered by any other insurance policy taken out and maintained by the Purchaser or in respect of which the Purchaser has a contractual obligation to do so; and/or

(d) loss and/or damage to the equipment which is consistent with the use by the Purchaser of the Equipment:

(i) in compliance with the Maintenance and Servicing Requirements; and

(ii) in compliance with the Usage Cycle Parameters; and

(iii) in compliance with the Use Parameters; and

(iv) having only carried out Authorised Repairs to the Equipment; and

(v) having all and any replacement parts fitted by the Warrantor; and

(vi) in unmodified form.

06. LIMITATION OF LIABILITY

6.1 The Warrantor's liability to the Purchaser shall be limited as follows:

(a) The Warrantor shall not in any circumstances be liable to the Purchaser for indirect and/or consequential and/or economic loss suffered and/or incurred as the case may be by the Purchaser; and

(b) The Warrantor shall only be liable to the Purchaser for the reasonable and proper costs reasonably and properly incurred by the Purchaser directly in connection with the repair and/or replacement (at the Warrantor's absolute discretion) of the Equipment or any part of the Equipment; and

(c) The Warrantor's liability to the Purchaser shall notwithstanding any other provision of this Warranty, not in any circumstances exceed the Purchase Price of the Equipment.

07. WARRANTY CLAIMS

7.1 The Purchaser shall in respect of any claim against the Warrantor under this Warranty and within 24 hours of the occurrence of the subject matter of the Warranty Claim:

(a) Complete in full and submit to the Warrantor a Warranty Claim in the form annexed to Schedule 4;

(b) Provide date stamped or date identifiable photographs evidencing the claim; and

(c) Make the Equipment or the relevant part of the Equipment available to the Warrantor for inspection within 48 hours of notification of the relevant Warranty Claim.

08. ENTIRE AGREEMENT

8.1 This Warranty constitutes the entire agreement between the parties and supersedes and extinguishes all previous promises, assurances, warranties, representations and understandings between them, whether written or oral, relating to its subject matter.

8.2 Each party agrees that it shall have no remedies in respect of any statement, representation, assurance or warranty (whether made innocently or negligently) that is not set out in this Warranty. Each party agrees that it shall have no claim for innocent or negligent misrepresentation or negligent misstatement based on any statement in this Warranty.

No variation of this Warranty shall be effective unless it is in writing and signed by the parties (or their authorised representatives).

09. WAIVER

No failure or delay by a party to exercise any right or remedy provided under this Warranty or by law shall constitute a waiver of that or any other right or remedy, nor shall it prevent or restrict the further exercise of that or any other right or remedy. No single or partial exercise of such right or remedy shall prevent or restrict the further exercise of that or any other right or remedy.

10. SEVERANCE

10.1 If any provision or part-provision of this Warranty is or becomes invalid, illegal or unenforceable, it shall be deemed deleted, but that shall not affect the validity and enforceability of the rest of this Warranty.

10.2 If any provision or part-provision of this Warranty is deemed deleted under clause 10.1 the parties shall negotiate in good faith to agree a replacement provision that, to the greatest extent possible, achieves the intended commercial result of the original provision.

11. THIRD PARTY RIGHTS

11.1 This Warranty does not give rise to any rights under the Contracts (Rights of Third Parties) Act 1999 to enforce any term of this Warranty.

12. GOVERNING LAW

12.1 This Warranty and any dispute or claim (including non-contractual disputes or claims) arising out of or in connection with it or its subject matter or formation shall be governed by and construed in accordance with the law of England and Wales.

13. JURISDICTION

13.1 Each party irrevocably agrees that the courts of England and Wales shall have exclusive jurisdiction to settle any dispute or claim (including non-contractual disputes or claims) arising out of or in connection with this Warranty or its subject matter or formation.

DESIGN CONFORMITY (EC & UK)

(01) This certificate meets the requirements of the Machinery Directive 2023/42/EC of the European Parliament and Council.

(02) This certificate meets the requirements of the Supply of Machinery (Safety) Regulations 2008.

DETAILS

NAME & ADDRESS OF MANUFACTURER:
Conquip Engineering Group Ltd, Unit 4, Waterbrook Estate, Alton, Hampshire. GU34 2UD

NAME & ADDRESS OF PERSON TO COMPILE TECHNICAL FILE:
Name: Daniel Critchley Address: Conquip Engineering Group, Unit 4, Waterbrook Estate, Alton, Hampshire. GU34 2UD

NAME & ADDRESS OF AUTHORISED REPRESENTATIVE IF ONE HAS BEEN MANDATED BY THE MANUFACTURER:
N/A

NAME, ADDRESS, AND IDENTIFICATION NUMBER OF THE NOTIFIED BODY (01) OR APPROVED BODY (02), WHERE APPLICABLE:
N/A

EQUIPMENT DESCRIPTION

PRODUCT CODE(S)	GENERAL DESCRIPTION	WORKING LOAD LIMIT
CS255AA	Concrete Washout Frame	Self Weight

HARMONISED STANDARDS & REGULATIONS

ITEM	CODE	DESCRIPTION
EC DIRECTIVE/ REGULATION	2023/42/EC	Directive 2023/42/EC- new machinery directive
HARMONISED STANDARDS	BS EN ISO 12100:2010	Safety of machinery General principles for design Risk assessment and risk reduction
OTHER REGULATIONS	LOLER 1998	Lifting Operations and Lifting Equipment Regulations 1998 (LOLER)
	PUWER 1998	Provision and Use of Work Equipment Regulations 1998 (PUWER)

DECLARATION

PLACE OF DECLARATION:
Alton

DATE OF DECLARATION:
June 2026

I declare that the above equipment meets the Essential Health and Safety requirements of the

(01) Machinery Directive 2023/42/EC of the European Parliament and Council.

(02) Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc. Act 1974.

NAME:	POSITION:	SIGNATURE:
Daniel Critchley	Chief Executive Officer	

TALKING TO US IS EASY

WE'RE HERE TO HELP

Call us on 0333 300 3470
Email us at sales@cqegroup.com
www.cqegroup.com

Copyright © 2026 Conquip Engineering Group. All Rights Reserved.
Concrete Washout Frame - Issue 01