TECHNICAL DATA SHEET

ESCAPE SET



INTRODUCTION

OVERVIEW

The Conquip Escape Set is a breathing apparatus used to provide clean oxygen whilst safely exiting hazardous environments in an emergency.

Simple to fit, it operates automatically, providing a constant flow of oxygen to the operative for up to 15 minutes, preventing the inhalation of smoke or toxic fumes.

KEY BENEFITS

- Photoluminescent panels and reflective stripes make the unit easy to locate when visibility is limited.
- A fail-safe reducer provides constant airflow, with an alarm whistle warning before the air supply runs out.
- Flame-resistant hood and large visor provide protection and wide peripheral vision.
- Robust, washable materials withstand harsh conditions while allowing water to drain freely.
- Transparent viewing windows allow cylinder pressure to be checked without unpacking the unit.
- Complies with BS EN1146:2005, Lloyd's Register Certificate of Fire Approval and Lloyd's Register Certificate of Type Approval. Plus, SOLAS Chapter II-2, the Marine Equipment Directive, the Pressure Equipment Directive and ISO 23269-1:2008.

support@cqegroup.com | +44 (0) 333 300 3470 | www.cqegroup.com

PRODUCT INFORMATION

SPECIFICATION

ITEM	PRODUCT CODE
15-Minute Escape Set	PE146



DIMENSIONS (mm)			HOOD AIRFLOW (litres/min)	OPERATING TEMPERATURE (°C)		WEIGHT* (kg)	CYLINDER PRESSURE (bar)	CYLINDER CAPACITY (litres)
L	H	T		MIN	MAX			
510	260	190	35-37	-15	+60	5.2	200	3

*Weight includes cylinders

support@cqegroup.com | +44 (0) 333 300 3470 | www.cqegroup.com

TALKING TO US IS EASY

WE'RE HERE TO HELP

Call us on 0333 300 3470
Email us at sales@cqegroup.com
www.cqegroup.com

Copyright © 2026 Conquip Engineering Group. All Rights Reserved.
Escape Set - Issue 01