SPECIFICATION SHEET

GUARDIAN GOALPOSTS



INTRODUCTION

OVERVIEW

Guardian Goalposts provide a high-visibility, temporary height-restriction system to help prevent vehicles, plant and equipment from contacting overhead power lines. Ideal for construction sites, roadworks and utility operations, they define safe access clearances at site entrances and vehicle routes.

Constructed from lightweight, non-conductive glass-reinforced polyester (GRP) or fibreglass, the telescopic poles are adjustable to the required clearance height. High-visibility markings, optional photoluminescent sections and illuminated bunting enhance visibility in low-light conditions.

Available with galvanised steel bases, concrete retention sockets or water or sand-fillable ballast blocks, Guardian Goalposts offer flexible installation and efficient deployment, supporting overhead power line safety measures in accordance with Health and Safety Executive (HSE) GS6 guidance.

KEY BENEFITS

- Designed in accordance with UK HSE GS6 guidance for preventing danger from overhead power lines.
- Manufactured from lightweight, non-conductive glass-reinforced polyester (GRP) or fibreglass components, with electrical insulation properties specified by the manufacturer to reduce electrical risk.
- Extendable pole assembly allows adjustment to the required carriageway clearance height. Designed for rapid deployment and adjustment by a single operator within minutes, subject to installation conditions.
- Feature high-contrast red and white markings. Optional photoluminescent sections and illuminated bunting systems are available to enhance visibility in low-light and night-time working conditions.
- Available in four variations with steel or filled base options that provide stability and resistance to wind loading, and bunting or solid crossbar options that offer varying widths.
- Suitable for a range of applications including construction, highways, utilities and railways.

PRODUCT INFORMATION

SPECIFICATION



TYPE	WIDTH* (mm)		HEIGHT (mm)		WEIGHT (kg)
	CROSSBAR	BUNTING	CLOSED	EXTENDED	
Steel Base + Bunting	7600	25,000	1800	7300	34
Steel Base + Crossbar					38
Filled Base + Bunting	7600	25,000	1800	7300	118
Filled Base + Crossbar					122

*Wdith between two posts secured together.

support@cqegroup.com | +44 (0) 333 300 3470 | www.cqegroup.com

TALKING TO US IS EASY

WE'RE HERE TO HELP

Call us on 0333 300 3470
Email us at sales@cqegroup.com
www.cqegroup.com

Copyright © 2026 Conquip Engineering Group. All Rights Reserved.
Guardian Goalposts - Issue 01